



light dark

COLLECTION
2022/23

LIGHT



DARK

In an evocation of luxury and elegance, c

interior design creates dramatically finer
technologies.



ligCOLhLECTIOtN da

ANTIQ
LIGHT - DARK - EG

A reposition ceramic tiles at the
forefront of contemporary
interior design and decoration.









Size :
600x1200mm

Finish :
Glossy

Random :
04

ANTIQ
LIGHT



ANTIQ
DARK





ligCOLhLECTIOtN da



ANTRESIT LIGHT -
DARK - EG

A reposition ceramic tiles at the
forefront of contemporary
interior design and decoration.





Size :
600x1200mm

Finish :
Glossy

Random :
04

ANTRESIT
LIGHT



ANTRESIT
DARK





ligCOLhLECTIOtN da



AQUARIS LIGHT -
DARK - EG

A reposition ceramic tiles at the
forefront of contemporary
interior design and decoration.









Size :
600x1200mm

Finish :
Glossy

Random :
04

AQUARIS
LIGHT



AQUARIS
DARK





ligCOLhLECTIOtN da



ARISTOC LIGHT
- DARK - EG

A reposition ceramic tiles at the
forefront of contemporary
interior design and decoration.







Size :
600x1200mm


Finish :
Glossy

Random :
04

ARISTOC BLUE
LIGHT



ARISTOC BLUE
DARK





ligCOLhLECTIOtN da

BAZEL LIGHT
- DARK - EG

A reposition ceramic tiles at the
forefront of contemporary
interior design and decoration.









Size :
600x1200mm



Finish :
Glossy

Random :
04

BAZEL
LIGHT



BAZEL
DARK





ligCOLhLECTIOtN da

DOVER LIGHT
- DARK- EG

A reposition ceramic tiles at the
forefront of contemporary
interior design and decoration.








Size :
600x1200mm


Finish :
Glossy

Random :
04

DOVER
LIGHT



DOVER
DARK





ligCOLhLECTIOtN da

ELCTEC LIGHT -
DARK- EG

A reposition ceramic tiles at the
forefront of contemporary
interior design and decoration.

MARQUIS








Size :
600x1200mm




Finish :
Glossy

Random :
04

ELCTEC
LIGHT



ELCTEC
DARK





ligCOLhLECTIOtN da

ELECTRA LIGHT -
DARK- EG

A reposition ceramic tiles at the
forefront of contemporary
interior design and decoration.








Size :
600x1200mm


Finish :
Glossy

Random :
04

ELECTRA
LIGHT



ELECTRA
DARK





ligCOLhLECTIOtN da

IRON LIGHT -
DARK- EG

A reposition ceramic tiles at the
forefront of contemporary
interior design and decoration.








Size :
600x1200mm




Finish :
Glossy

Random :
04

IRON
LIGHT




IRON
DARK





ligCOLhLECTIOtN da



PIZARO LIGHT -
DARK- EG

A reposition ceramic tiles at the
forefront of contemporary
interior design and decoration.








Size :
600x1200mm

Finish :
Glossy

Random :
04

PIZARO
LIGHT




PIZARO
DARK





ligCOLhLECTIOtN da



SEANA LIGHT
- DARK- EG

A reposition ceramic tiles at the
forefront of contemporary
interior design and decoration.








Size :
600x1200mm

Finish :
Glossy

Random :
04

SEANA
LIGHT



SEANA
DARK





TECHNICAL SPECIFICATION

PACKING DETAILS

SR. NO	PRODUCT	NOMINAL SIZE	TILES PER BOX	COVERAGE AREA
1	VITRIFIED TILES	600x1200mm	2	1.44 Sq. Mtr.

CHARACTERISTIC	STANDARD AS PER ISO-13006/EN 14411 GROUP BIa	MEAN VALUE OF POLISHED GVT	MEAN VALUE OF RUSTIC GVT	TEST METHOD
REGULATORY PROPERTIES				
Deviation in length & width	±0.5 %	±0.1 %	±0.1 %	ISO-10545-2
Deviation in thickness	±5.0 %	±4.0 %	±4.0 %	ISO-10545-2
Straightness in side	±0.5 %	±0.1 %	±0.1 %	ISO-10545-2
Rectangularity	±0.5 %	±0.1 %	±0.1 %	ISO-10545-2
Surface flatness	±0.5 %	±0.2 %	±0.2 %	ISO-10545-2
Color difference	Unaltered	No change	No change	ISO-10545-16
Glossiness	As per mfg	Min 90%	Min 4%	GLOSSOMETER
STRUCTURAL PROPERTIES				
Water absorption	< 0.50 %	< 0.20 %	< 0.20 %	ISO-10545-3
Apparent density	> 2.0 g/cc	>2.10 g/cc	>2.10 g/cc	DIN 51082
MASSIVE MECHANICAL PROPERTIES				
Modulus of rupture	Min. 35 N/mm ²	Min. 40 N/mm ²	Min. 40 N/mm ²	ISO-10545-4
Breaking strength	Min. 1300 N	Min. 2000 N	Min. 2000 N	ISO-10545-4
Impact resistance	As per mfg.	Min. 0.55	Min. 0.55	ISO-10545-5
SURFACE MECHANICAL PROPERTIES				
Surface abrasion resistance	As per mfg.	Min. Class-3	Min. Class-4	ISO-10545-7
MOH's hardness	As per mfg.	Min. 4	Min. 5	EN 101
THERMO HYGROMETRIC PROPERTIES				
Frost resistance	No damage	No damage	No damage	ISO-10545-12
Thermal shock resistance	No damage	No damage	No damage	ISO-10545-9
Moisture expansion	Nil	Nil	Nil	ISO-10545-10
Thermal expansion (COE)	Max. 9.0 x 10 ⁻⁶	Max. 6.5x10 ⁻⁶	Max. 6.5 x 10 ⁻⁶	ISO-10545-8
Crazing resistance	As per mfg.	Min. 10 Cycle	Min. 10 Cycle	ISO-10545-11
CHEMICAL PROPERTIES				
Chemical resistance	No damage	No damage	No damage	ISO-10545-13
Stain resistance	Resistant	Resistant	Resistant	ISO-10545-14
SAFETY PROPERTIES				
Slip resistance	As per mfg.	>0.40	>0.40	ISO-10545-17
Fire resistance	As per mfg.	Fire proof	Fire proof	N. A.
Lead & Cadmium given off by glazed tiles	As per mfg.	Does not yield Pb & Cd	Does not yield Pb & Cd	ISO-10545-15

