

COLLECTION COLLECTION 600X1200 mm





the freed give for the four ideas



technology

KILN-DLT
PRESS- HLT
POLISING-KEDA
DIGITAL-SYSTEM



unma

Our exceptional standards of precision are set by our technologies to lead your space to per fection.

Droduct FEATURES & APPLICATIONS





RESISTANT TO ICE AND FROST



FIRE &
HIGH-TEMPERATURE
RESISTANT



SCRATCH & IMPACT RESISTANT



CHEMICAL & STAIN RESISTANCE



UNALTERABLE TO UV RAYS





EASY TO CLEAN



100%
NATURAL &
RECYCLABLE





HOME INDOOR



EXTERNAL CLADDING



SHOP & BOUTIQUE




OFFICE BUILDING




HOSPITALITY



COMMERCIAL SPACE






CUBIX BROWN-EG




CUBIX BEIGE-EG



CUBIX GREY-EG



CUBIX BIANCO-EG






astra grey

A PERFECT RECREATION OF ELEGANCE.


ASTRA CREMA

ASTRA BIANCO

ASTRA GREY-EG




ASTRA CREMA-EG



ASTRA BIANCO-EG





cemento choko


RECREATION OF ELEGANCE.

CEMENTO BEIGE


CEMENTO GREY

CEMENTO GRIS


CEMENTO CHOKO-EG




CEMENTO BEIGE- EG



CEMENTO GREY-EG



CEMENTO GRIS-EG





clara wood brown

A PERFECT

RECREATION OF ELEGANCE.


CL ARA
WOOD BEIGE

CLARA WOOD BROWN-EG



CLARA WOOD BEIGE- EG_






corus crema


RECREATION OF ELEGANCE.

CORUS CREAMA

CORUS CREMA-EG



CORUS BIANCO-EG






RECREATION OF ELEGANCE.


FLORNCE BIANCO

FLORNCE GREY


FLORNCE CREMA- EG




FLORNCE BIANCO- EG.




FLORNCE GREY-EG





MARBO CHOKO-EG



MARBO BEIGE-EG




MARBO GRIS-EG




MARBO ROSO-EG




MARBO GREY- EG







TRACKS GREY- EG




TRACKS CREMA- EG



TRACKS BIANCO- EG



TRACKS BROWN- EG





TECHNICAL SPECIFICATION

PACKING DETAILS

SR. NO	PRODUCT	NOMINAL SIZE	THICKNESS	TILES PER BOX	COVERAGE AREA
1	VITRIFIED TILES	600x1200mm	9 mm	2	1.44 Sq. Mtr.

CHARACTERISTIC	STANDARD AS PER ISO-13006/EN 14411 GROUP Bla	MEAN VALUE OF POLISHED GVT	MEAN VALUE OF RUSTIC GVT	TEST METHOD				
REGULATORY PROPERTIES	ı	ı						
Deviation in length & width	±0.5 %	±0.1 %	±0.1 %	ISO-10545-2				
Deviation in thickness	±5.0 %	±4.0 %	±4.0 %	ISO-10545-2				
Straightness in side	±0.5 %	±0.1 %	±0.1 %	ISO-10545-2				
Rectangularity	±0.5 %	±0.1 %	±0.1 %	ISO-10545-2				
Surface flatness	±0.5 %	±0.2 %	±0.2 %	ISO-10545-2				
Color difference	Unaltered	No change	No change	ISO-10545-16				
Glossiness	As per mfg	Min 90%	Min 4%	GLOSSOMETER				
STRUCTURAL PROPERTIES								
Water absorption	< 0.50 %	< 0.20 %	< 0.20 %	ISO-10545-3				
Apparent density	> 2.0 g/cc	>2.10 g/cc	>2.10 g/cc	DIN 51082				
MASSIVE MECHANICAL PROPERTIES								
Modulus of rupture	Min. 35 N/mm²	Min. 40 N/mm ²	Min. 40 N/mm²	ISO-10545-4				
Breaking strength	Min. 1300 N	Min. 2000 N	Min. 2000 N	ISO-10545-4				
Impact resistance	As per mfg.	Min. 0.55	Min. 0.55	ISO-10545-5				
SURFACE MECHANICAL PROPERTIES								
Surface abrasion resistance	As per mfg.	Min. Class-3	Min. Class-4	ISO-10545-7				
MOH's hardness	As per mfg.	Min. 4	Min. 5	EN 101				
	, p							
THERMO HYGROMETRIC PROPERTIES								
Frost resistance	No damage	No damage	No damage	ISO-10545-12				
Thermal shock resistance	No damage	No damage	No damage	ISO-10545-9				
Moisture expansion	Nil	Nil	Nil	ISO-10545-10				
Thermal expansion (COE)	Max. 9.0 x 10 ⁻⁶	Max. 6.5x10 ⁻⁶	Max. 6.5 x 10 ⁻⁶	ISO-10545-8				
Crazing resistance	As per mfg.	Min. 10 Cycle	Min. 10 Cycle	ISO-10545-11				
CHEMICAL PROPERTIES	IEMICAL PROPERTIES							
Chemical resistance	No damage	No damage	No damage	ISO-10545-13				
Stain resistance	Resistant	Resistant	Resistant	ISO-10545-14				
SAFETY PROPERTIES	AFFTY PROPERTIES							
Slip resistance	As per mfg.	>0.40	>0.40	ISO-10545-17				
Fire resistance	As per mfg.	Fire proof	Fire proof	N. A.				
Lead & Cadmium given off by glazed tiles	As per mfg.	Does not yield Pb & Cd	Does not yield Pb & Cd	ISO-10545-15				

